

PATENT SPECIFICATION

(11) 1445 143

1445 143

- (21) Application No. 49515/73 (22) Filed 24 Oct. 1973
 (31) Convention Application No. 303168 (32) Filed 2 Nov. 1972 in
 (33) United States of America (US)
 (44) Complete Specification published 4 Aug. 1976
 (51) INT CL² G03G 15/16
 (52) Index at acceptance

G2H 12 1F 1LY 1Y 2B 2Y 7D 7F 7Y 8F1 8FY 8G1A
 8G1Y 8GY 8Y



(54) ELECTROPHOTOGRAPHIC TONER TRANSFER AND FUSING APPARATUS AND METHOD

(71) We, ITEK CORPORATION, a corporation organised and existing under the laws of the State of Delaware, United States of America, of 10 Maguire Road, Lexington, Massachusetts, United States of America, do hereby declare the invention, for which we pray that a patent may be granted to us, and the method by which it is to be performed, to be particularly described in and by the following statement:—

This invention relates to electrophotographic transfer-fusing apparatus and more particularly to an improved electro-photo-graphic toner transfer-fusing apparatus of the thermomechanical type.

In customary electrophotographic processes, a conductive backing having a photoconductive insulating layer thereon is electrostatically imaged by first uniformly charging its surface, and subsequently exposing the charged surface to a pattern of activating electromagnetic radiation, such as light. The radiation pattern selectively dissipates electrostatic charges in the illuminated areas on the photoconductive surface, which results in a latent electrostatic image in non-illuminated areas. This latent electrostatic image can be subsequently developed to form a visible image by depositing developer materials thereon by a variety of development techniques, the most common of which is cascade development.

Solid electrophotographic developer materials are often two-component systems containing finely divided pigmented particles, commonly called "toner", and relatively coarser, larger beads, commonly called "carrier beads". Toner particles and carrier beads are chosen or modified to make them triboelectrically dissimilar, so that triboelectric charges are generated upon each as they are transported through the development apparatus. Additionally, the components are chosen so that the toner will have triboelectric charges thereon opposite in sign to the electrostatic charge pattern to be developed. Thus, toner particles adhere to the carrier particles because of their electrostatic charges and because of van der Waals forces, until they

are shaken loose during development and captured by the opposite and stronger electrostatic charges on the insulating surface to be developed.

Developed toner images can be fused to the photoconductive insulating surface, or transferred and fused to another substrate such as plain paper. Transfer of the toner image can be accomplished by electrostatic methods, by the use of adhesive-coated paper, by pressure contact, etc. Once transferred, the toner image can be fused or fixed to the paper by heating and cooling, solvent vapor fusing, applying a fixative coating over the image, etc. The general state of the art in transfer and fusing methods and apparatus is described in more detail in Schaffert, *Electrophotography*, Focal Press New York, (1965) at pages 24—25 and 39—40; and in the following U.S. Patents: Lorenz, U.S. 3,640,749; Welkel, U.S. 3,647,292; Colt et al., U.S. 3,647,499; Young, U.S. 3,640,249; Eastman, U.S. 3,630,591; Tyler, U.S. 3,612,685; Langdon, U.S. 3,612,677; Vince, U.S. 3,584,195; Schluntz, U.S. 3,558,853; White et al., U.S. 3,567,484; Fantuzzo, U.S. 3,566,076; and Byrne, U.S. 3,539,161.

In some cases, toner images have been transferred to intermediate belts prior to fusing on copy paper. Carlson, U.S. 2,990,278, for example, teaches the use of an intermediate transfer belt which has a smoother surface and which does not form a mechanical bond with toner. Carlson, U.S. 3,374,769 teaches the use of a transparent intermediate belt with a reflecting surface on the side of the belt opposite to a radiant heater. The transfer and fusing system described herein has advantages over these prior art systems.

One of the more recent efforts to improve pressure transfer and fusing techniques is described in Byrne, U.S. Patent 3,591,276. In the method described therein, a developed xerographic powder image is transferred from a photoconductive surface to a final support material such as paper by contacting the toner image on the photoconductor with an elastic material under pressure to encapture

the toner image due to the deformation of the elastomeric member. Subsequently, the toner image is transferred from the elastomeric member onto paper, either preheated or heated simultaneously by bringing the paper into pressure contact with the elastomeric member. Sufficient heat is supplied to the paper prior to or during pressure contact to cause the toner particles to melt and coalesce onto the paper.

While the techniques described by Byrne have improved pressure transfer and fusing, significant problems still remain. For example, since the paper is required to be significantly heated prior to or during transfer, high amounts of power are required especially since the paper normally contains moisture which must be driven off. Thus, high amounts of heat have to be supplied because of the use of an inefficient method of heating the toner. This results in a corresponding loss of economy and also causes certain other undesirable limitations for copy processes. Additionally, there can be a loss in the quality of fusing obtainable because of certain inherent limitations on the combination of heat and pressure which can be applied when preheated paper is depended upon to heat the toner to its melting point. In general, these inherent limitations arise because the paper can be heated only so high and because steep pressure pulses are not used at the transfer point.

Another recent effort to improve pressure transfer and fusing techniques is described in Sanders et al., U.S. 3,669,706. The fusing device described therein has a radiant energy transmissive rotatable drum covered by a radiant energy transmissive resiliently compressible layer and a thin flexible radiant energy absorbing outer skin. A major drawback to this system is its inefficient thermal design. For example, the compressible layers are purposely designed to absorb large amounts of heat since the inner layer is relatively thick and since the outer layer is radiation absorbing. Also, thermal inefficiency occurs since a drum substrate is required between the heat source and toner, and because heat is applied to the bottom side of the toner. Since the drum heats up, the concomitant disadvantage of lessening the life of the photoconductor is also present. Higher pressure at the transfer point is also required, since heat passes from the drum surface to the toner by conductive heating rather than radiation heating; thick layers make it difficult, however, to achieve a pressure pulse with a fast rise time. Additionally, since the elastomer is relatively thick, dimensional distortion of the image is increased.

It is desirable, therefore, to have toner transfer and fusing methods and apparatus which can take advantage of the improvements offered by Byrne and Sanders et al.

while not suffering from their inherent disadvantages.

The preferred embodiment of this invention may be referred to as a xerographic heat and pressure transfer and fusing apparatus. It includes an intermediate transfer member which has a smooth surface, a surface free energy below 40 dynes per centimeter, a hardness from 3 to 70 durometers and a heat capacity of below 3.1×10^{-2} calories/cm²/°C.

Means are provided for transferring a toner image from a first support material onto the surface of the intermediate transfer member. The toner image on the intermediate transfer member is then heated, preferably selectively, to a temperature at which it will flow when a sufficient force is applied thereto. Selective heating can be accomplished by means of a radiant heater and the proper choice of an intermediate material. A second support material, supplied for example on rolls, is then brought into pressure contact with the heated toner on the intermediate transfer member. Preferably, a pressure applying element is positioned immediately after the radiant heating zone to apply a pressure pulse with a steep rise time. Preheating toner and the use of intermediate transfer members as described herein results in good toner transfer and fusing, especially when the toner is selectively heated and the force is applied in such a manner that the resulting pressure pulse has a steep rise time.

This new transfer and fusing apparatus has advantages over those of the prior art. For example, higher resolution in the final copy can be attained with this transfer-fusing apparatus than with most others. This is important because new xerographic techniques have been recently developed which allow the formation of higher resolution toner images, but these images must be transferred and fused without significant losses in resolution or the improvement is lost. Electrostatic transfer methods appear to be limited in the resolution which can be obtained.

Additionally, paper handling, typically a serious problem in electrophotographing copiers, is simplified. This results partly because the necessity of handling paper carrying non-fused toner images, which is characteristic of many prior art techniques, has been eliminated. Additionally, the necessity to electrostatically tack copy paper to a photoconductive surface is eliminated, thereby obviating the troublesome problem of having sheets of paper stick together even after they exit from the machine because of residual charges thereon.

Also, because the toner image is transferred mechanically, a variety of substrates can be used. These include both conductive and non-conductive substrates. Since the second support material is merely passed between two

pressure rollers, substrates can be used which are not flexible, and even delicate materials can be used by creating very gentle transfer conditions.

5 Another advantage to the transfer and fusing apparatus described herein is that the second support material, typically paper, carries heat out of the machine. In this regard, the paper acts as a heat sink so that heat
10 can be transferred from the hot toner and intermediate member to the paper which then exits from the machine. Because of this, parts of the copy machine tend to heat up to a much lesser degree.

15 In addition to the above advantages over previously known state of the art toner transfer and fusing apparatus, the apparatus described herein has several significant advantages over the elastomeric systems described
20 in the Byrne ('276) and Sanders et al. ('706) patents. Thus, considerably less power is required because of the overall increase in thermal efficiency which is achieved due to selective preheating of the toner, designing
25 the transfer member to have a low heat capacity, etc. Additionally, the transfer from the first support material to the intermediate transfer member can be controlled by adjusting the pressure applied and the transfer
30 member used so that virtually any portion of the original toner image can be transferred from the photoconductor to the intermediate member. This is an important advantage not
35 only because less toner is used for each copy, but because image preservation, i.e., the ability to make multiple copies from one electrostatic latent image, becomes possible when
40 less than the entire toner image is transferred. An electrostatic latent image on the first support material, typically a photoconductive insulating material, can be continually developed and transferred in part to the intermediate
45 transfer member from where it can be essentially totally transferred and fused to a second support material, such as paper. Image preservation results in greater copying efficiency, faster production of copies, and tends, to wear the photoconductor less.

50 Further, since Byrne preheats or simultaneously heats copy paper to temperatures above the toner melting point, the paper cannot act as a heat sink to cool the transfer member. Thus, the transfer member has a tendency to
55 heat up which can interfere with toner transfer from the photoconductive surface and might even result in thermal damage to the delicate photoconductor.

In the accompanying drawings,

60 Figure 1 is a schematic illustration of a transfer-fusing apparatus of this invention employing an intermediate transfer belt;

Figure 2 is a schematic illustration of a transfer-fusing apparatus of this invention employing an intermediate transfer drum;

65 Figure 3 is a schematic illustration of a

transfer-fusing apparatus of this invention employing an intermediate transfer belt and a slidably engageable transfer roller behind the belt at the photoconductive surface;

70 Figure 4 is a partially cut-away perspective view of a section of an intermediate transfer belt useful with this invention;

75 Figure 5 presents representative plots of the heat transfer to and from copy paper, expressed as the temperature of the paper (T_p) versus time (t), in the different zones of apparatus of this invention and of the prior art;

80 Figure 6 presents representative plots of the heat transfer to and from a toner image, expressed as the temperature of the toner (T_t) versus time (t), in different zones of apparatus of this invention and of the prior art;

85 Figure 7 presents representative plots of pressure-time pulses of this and prior art transfer and fusing apparatus.

Referring now to the Figures in more detail, Figure 1 illustrates in schematic form a transfer-fusing apparatus of this invention. A
90 photoconductive insulating sheet, such as zinc oxide paper 1, with a developed but non-fused toner image 3 thereon, passes between rollers 5 and 7 which are caused to rotate with the same speed by motor 9. Toner image
95 3 is shown, for the purposes of illustration, as consisting of two layers of toner particles, though in fact there are usually more. The pressure between rollers 5 and 7 can be adjusted by spring means 10.

100 An intermediate transfer belt 11 is trained to pass over rollers 7, 12 and 13 in an endless loop. Belt 11 can be formed, for example, from a polyimide film substrate coated with 0.1—10 mils of silicone rubber or a fluoro-elastomer which provides a transfer member having a smooth, low surface free energy surface and a hardness between 3 and 70 durometers. The details of suitable transfer members are described in greater detail infra.

110 As zinc oxide sheet 1 carrying toner image 3 passes through the nip between rollers 5 and 7, part of toner image 3 is transferred to the surface of belt 11 as illustrated by the single layer of toner image 3'. This transfer is referred to as T_1 . By merely adjusting the pressure between rollers 5 and 7, and selecting a transfer member having the desired properties within the operable range, the amount of toner transferred at T_1 to the
115 intermediate member can be controlled. By adjusting the various parameters including pressure, the electrostatic latent image, and the surface characteristics and thickness of the transfer material, it is believed that the range
120 of toner transferred can be reasonably controlled from 20% toner transfer to 80% toner transfer. As a first approximation, the softer transfer materials and higher pressures
125

tend to result in higher amounts of toner transfer at T_1 , and vice versa.

As can be seen, part of toner image 3 is not transferred from zinc oxide sheet 1 and remains thereon as non-transferred toner image 3'. Toner image 3' can be redeveloped if an image preservation mode is desired, can be cleaned so that sheet 1 is reusable, or can simply be thrown away with sheet 1. Partially transferred toner image 3' passes next to a radiant heating zone formed by radiant heating elements 21 which are encompassed by a reflector 23. Radiant heating tends to selectively heat the toner. For maximum selective heating, it is of course desirable to use a belt 11 with a low heat absorption compared to that of toner image 3'. This is usually easily accomplished since commonly used toners are pigmented black, and since it is easy to obtain belt material which is colorless and transparent or pigmented white.

The radiant heating zone is short and hot. Its length should be sufficient to provide a point on the transfer member with heating for 1/8 to 1/3 seconds, and it should be hot enough to provide at least 40 watts/square inch at a belt speed of 7 1/2 inches per second. The shorter, more compact, higher temperature heaters lose less energy than longer heaters thereby making them more efficient.

A second support material, such as paper 25, is supplied from a feed roll 27. Paper 25 is brought into pressure contact with intermediate belt 11 by pressure bar 29 at a point closely adjacent to where partial toner image 3' exits from the radiant heating zone. This is to avoid any unnecessary radiation from the image to the surrounding atmosphere prior to transfer and fusing.

Pressure bar 29 has a beveled front edge leading to a flat trailing edge to guide paper 25 into a narrow point of contact, T_2 , which is where toner is transferred from intermediate belt 11 to paper 25. The width of the flat trailing edge of pressure applying bar 29 is kept narrow so that the pressure pulse at T_2 has a steep rise time. It has been found that the application of pressure in this manner tends to drive heated toner into the cold paper before the toner has a chance to cool below its solidification point. Thus, a mechanical bond between paper and toner can be formed even before the toner solidifies in the paper. This combination of pressure pulse and preheating of the toner has been found to provide excellent transfer and fusing of toner images.

After transfer and fusing has taken place at T_2 , paper 25 is held in contact with intermediate belt 11 and directed around guide roller 28 to a paper cutter 33 which cuts the paper to copy length. Paper 25 and belt 11 are allowed to remain in contact for a period after T_2 but prior to cutter 33 so that

heat can be transferred from belt 11 to paper 25 and subsequently out of the machine. This extended cooling zone is a feature of the transfer-fusing apparatus described herein, because it turns the previously penalizing high heat capacity of paper to a useful purpose. Normally, the paper and belt should remain in contact for at least 0.5 seconds or more for adequate cooling. The extended cooling zone also makes it possible to use the transfer belt as part of the paper transport system.

A completed electrophotographic copy 35, having a plain paper substrate 25 and an integrally fused toner image 3' thereon exits from the copy machine carrying most of the heat supplied to the toner and belt with it. Because of this, intermediate belt 11 returns around roller 13 to roller 7 for the next transfer of a developed xerographic image in a substantially cooled state.

Referring now to Figure 2, a copying machine is schematically illustrated wherein an intermediate transfer drum is used and wherein the apparatus is designed to operate in an image preservation mode, i.e., to produce multiple copies from a single imaging of the photoconductive drum 50. Typically, the photoconductive drum will consist of a conductive metal substrate 51, such as aluminum, coated on its outer surface with a layer of photoconductive insulating material 52, typically vitreous selenium. Drum 50 rotates about its axis and is shown rotating in a counterclockwise or "downhill" direction. Cleaning brush 55, which is mounted on slidable element 56 so that it can be disengaged, removes residual toner from the surface of drum 50 as desired.

A uniform electrostatic charge is formed on the surface of drum 50 by means of corona charging unit 57 which is electrically connected to a power source such as battery 58 and to ground. Uniformly electrostatically charged drum 50 then passes an imaging station 60 consisting of light sources 61, imaging lens 62 and slit 64, which serve to image original 63 onto the surface of drum 50.

Development of the electrostatic latent image thus produced is effected by cascade development apparatus 65. Typically, cascade development apparatus 65 will include a housing 66 including within it a bucket elevator system formed by an endless belt 67 having buckets 68 thereon. Electrostatic developer is lifted from a reservoir section 69 in buckets 68 to a point at the upper portion of drum 50 and is cascaded over the drum surface by means of feed guide 70. As developer cascades over drum 50, toner particles separate from the carrier beads and deposit on the drum surface in accordance with the latent electrostatic image thereon, thus forming a visible toner image. Spent developer is guided back into reservoir 69 by guide 71. A biased

development electrode 72 is shown closely spaced to the drum surface to improve solid area coverage.

Other means of forming electrostatic latent images on insulating surfaces are known in the art and may be used instead of the ones specifically illustrated. More specific details on suitable photoconductive elements, charging means, exposing means, and developing means can be found in the following U.S. Patents: 3,277,957; 3,312,548; 3,552,848; 3,566,108; 3,598,991; 3,612,864; 3,615,128; 3,628,786; 3,611,992; 2,832,311. In many prior art copying machines, the developed electrostatic image is transferred directly from the photoconductive surface to the final copy medium, which is usually paper. Typical prior art transfer systems are illustrated in U.S. Patents 3,584,195; 3,642,362 and 3,647,292.

An intermediate transfer drum 80 is used to remove a toner image from the surface of drum 50 and to transfer and fuse the toner image onto a final copy medium. Intermediate transfer drum 80 can be formed from a drum support material 81, such as aluminum, covered with a transfer material 82 having the transfer properties required as described below. Corona charge unit 83 is used to neutralize any residual electrostatic charges on the surface of drum 80 prior to each transfer at T_1 . Additionally, drum 80 is preferably connected to ground. Drum 80 is rotated in a clockwise manner and is positioned so that the surface of transfer material 82 comes into pressure contact with the surface of drum 50 at T_1 . As the toner image on the surface of drum 50 contacts the surface of transfer material 82, a portion of the toner image is transferred onto the surface of transfer material 82. As explained above, the amount of the toner image on the surface of drum 50 which is transferred at this point can be controlled by adjusting the pressure between the drum surfaces and by choosing a transfer material 82 having the properties required to do the desired transferring.

After a toner image has been transferred to the surface of drum 80, it passes by a radiant heater 85 consisting of heating elements 86 and reflector 87 which preferentially and selectively heat the toner image on the surface of transfer material 82 to a temperature above its melting point.

A second support material, such as paper 88 is supplied from paper roll 89 and is directed by guide roller 90 to pressure applying assembly 92. Guide roller 90 is also a heated roller which serves to preheat paper 88. Paper 88 is preheated only to a temperature, however, substantially below the toner melting point. In this way, the heat transfer rate from toner to paper can be reduced, thereby providing more time for transfer before the toner starts to cool below its melt-

ing point. Assembly 92 consists of a larger back up roller 93 and a smaller pressure roller 94, both of which are mounted off-axis to compensate for the forces applied to them by the rotation of drum 80. Small pressure roller 94 applies a pressure pulse at the point of contact, T_2 , having a fast rise time.

After transfer and fusing at T_2 , paper 88 is directed along intermediate transfer drum 80 by guide roller 95, whereby heat is transferred to the paper, and then to drive rollers 96 which direct the paper through cutter 97 which cuts the paper to copy lengths and deposits the copies 98 in a suitable collection tray 99.

As mentioned above, the copying machine illustrated in Figure 2 is designed to use image preservation, i.e., produce multiple copies from one optical imaging of the photoconductive drum. In this mode, cleaning brush 55 is initially used to clean the surface of the drum 50 and is then slidably disengaged from the drum surface as shown. Corona 57 applies a uniform electrostatic charge and an original 63 is imaged onto the surface of drum 50 by imaging station 60 after which the latent electrostatic image is developed by cascade developer 65. The developed image on drum 50 consists of multiple layers of toner. The pressure between the surface of drum 50 and transfer drum 80 is adjusted so that less than the whole amount of this toner image is transferred at T_1 . Good results in an image preservation mode have been obtained for example, when an amount of from 30% to 50% of the total toner image on the surface of drum 50 is transferred at T_1 . The toner image that is transferred to drum 80 is selectively heated by heater 85 and transferred onto the paper as shown. The remaining toner image on drum 50, which still persists in imagewise fashion, passes by disengaged cleaning brush 55, and by corona station 57 and imaging station 60 which are not operated. Upon passing by cascade developer 65, the depleted toner image is rejuvenated to a full toner image and is ready for another partial transfer to drum 80. By carefully choosing the conditions at T_1 and T_2 , a number of copies can be produced successfully from one optical imaging. This has many advantages which have been recognized by the art.

Referring now to Figure 3, a toner transfer and fusing apparatus is illustrated schematically using an intermediate transfer belt of the type illustrated in Figure 1.

Photoconductive drum 100 is shown without the other imaging developing and cleaning elements which are the same as or equivalent to those previously described. Intermediate transfer belt 102 is trained to pass in an endless loop around rollers 104, 106, 108 and 110. The belt can be driven, for example, by

motor 112 which drives roller 103 in a clockwise direction. Roller 104 can be adjusted by tensioning spring 114 to take up any slack created in intermediate transfer belt 102 caused by any dimensional changes due to variations in temperature thereof during, prior or subsequent to the copying process. Roller 110 is preferably constructed of hard rubber which is electrically leaky so that any background electric charges built up on belt 102, such as triboelectric charges built up between rollers and the belt, will dissipate naturally before the belt contacts photoconductor drum 100.

Transfer at T_1 , i.e., from the surface of photoconductive insulating drum 100 to the intermediate transfer member 102, is controlled by transfer roller 116 which is positioned at the back side of transfer belt 102 so that it can be moved in and out by adjusting tensioning spring 118. Thus, transfer roller 118 moves belt 102 into or out of contact with the photoconductive drum 100 at T_1 , and also regulates the pressure at T_1 . This provides a method for regulating the amount of toner transferred at T_1 without changing the surface characteristics of belt member 102. Pressure roller 116 can be formed from a relatively soft or a relatively hard material, but for the most flexibility it is preferably formed from a material having intermediate hardness.

Paper 120 is fed from paper roll 122 and brought into contact with the toner image on belt 102 at T_2 . Guide roller 124 directs the paper to pressure transfer assembly 128 consisting of large, interlocked rollers 129 and 130 and small roller 131 which rests on the larger rollers.

Roller 106 is a heated roller and serves to heat the toner image by supplying heat to belt 102 which in turn heats the toner image. Roller 106 can be constructed of a good heat conductor, such as aluminum, and can be heated by a resistance heater at its core.

After transfer at T_2 , paper 120 remains in contact with belt 102 for a time sufficient to provide cooling of the belt. Paper 120 is then directed by guide roller 132 away from the transfer-fusing apparatus.

Figure 4 illustrates an intermediate transfer belt suitable for use with this invention. It should be understood, of course, that such a member could be shaped in the form of a drum or other shape.

Intermediate transfer belt 150 is formed from substrate materials which must meet certain stringent physical requirements. Since most commonly used electrophotographic toners melt at about 90°C—130°C., these materials must exhibit good mechanical properties at the operating temperatures, which can reach 175°C. For example, material having an ultimate tensile strength of at least 5000 psi and a creep of below 3% under

a load of 1000 psi at 175° C is suitable. Suitable materials additionally should not exhibit significant distortion at such temperatures due to internal stress relief. It is also preferred that the substrate be flexible and have a low heat capacity.

One material which meets the above-mentioned stringent requirements is polyimide, which can be obtained in film form of suitable thicknesses from E. I. du Pont de Nemours and Co. under the trademark Kapton. Other high temperature polymers believed to have suitable mechanical properties include polyarylsulfones, polyamideimide, high temperature nylons, certain aromatic copolyesters such as produced by Carborundum under the trade name Ekkcel.

Metals such as stainless steel can also provide suitable substrates providing they can be formed into thin sheets or films having the required properties at elevated temperatures. Typically metals have relatively higher specific heats than polymer films, and accordingly, thinner sheets are used to keep the total heat capacity of the belt within the desired range. Thus, a 0.5 mil stainless steel substrate might be used instead of a 2 mil polyimide film.

The substrate is made reflective by applying a suitable coating 152 thereon. Thin aluminum or gold coatings are suitable, as well as others. This reflecting layer combined with a transparent transfer material provide the capability to selectively heat toner on the surface of the transfer member.

Intermediate transfer material 154 is integrally bound to substrate 151. Transfer material 154, as might be expected, has certain critical physical characteristics. Among these are a surface free energy of 40 dynes per centimeter or lower, a hardness ranging from 3 to 70 durometers, preferably 10—30 durometers (Shore A), and a surface which is smooth. Suitable materials include conductive and non-conductive silicone rubbers and fluoroelastomers. The exact surface properties, of course, will depend upon the transfer objectives and other design parameters.

Belt 150 is shown with conductive edges 156, which are optional but preferable. Conductive edges 156 insure that any buildup of background electrostatic charges, triboelectrically or otherwise, can be dissipated by connecting the edges 156 to ground. This can be achieved by using grounded conductive rollers which contact conductive edges 156, or by other alternative means. Typical thicknesses for suitable belts such as illustrated in Figure 4 include substrates of 0.5—5 mils coated with silicone rubber from 0.1 to 10 mils, and preferably 0.5—2 mils. The reflecting layer is very thin, typically about 300 Å.

The intermediate transfer members are designed to provide exceptional thermal efficiency in the transfer and fusing steps, as well

70

75

80

85

90

95

100

105

110

115

120

125

130

as throughout the entire copying process. Thus, materials, thicknesses, etc. are chosen to provide the member with a low heat capacity. This is achieved by keeping each of the layers as thin as is consistent with other parameters such as strength, and by using low specific heat materials. Preferred belts have total heat capacities, i.e. including all layers, of below 3.1×10^{-2} calories/cm²/°C.

Heat absorption in the substrate is eliminated or substantially diminished by coating it with the thin reflecting layer. The transfer surface can be made transparent to visible and infrared radiation by using silicone rubbers such as General Electric 615 or Dow Corning 3140; alternatively it can be made diffusely reflecting by using materials such as GE's RTV No. 11 silicone rubber, or Emerson and Cummings Nos. 4850 and 4451 silicone rubbers, these materials containing pigments or fillers such as silicone dioxide or titanium dioxide.

In regard to the transfer and fusion at T₂, i.e., from the intermediate transfer member to the final support material, there are several parameters involved in the transfer and fusing steps. The controlling parameters include the time and width of contact, force applied, surface free energy and hardness of the transfer material, the temperature of the toner and the toner's temperature-viscosity relationship. Thickness of the transfer material can also be important. Forces of between 2 and 40 lbs. per linear inch has been found to be effective.

Fusion results from forcing heated toner to flow into the copy paper to an appreciable depth and allowing it to cool and set therein. It has been found that outstanding fusion can be achieved using the apparatus described herein. This is believed to be due to the fact that the heated toner is physically driven into the paper before it can substantially cool, thereby allowing toner to adhere, upon cooling, to the paper substrate to a considerable depth, rather than merely to the surface fibers.

The controlling parameters with heat and pressure fusion as described herein include the temperature to which the toner is heated, the pressure which is applied, the rise time of the pressure pulse, the time of application of the pressure, and the length of the transfer zone. Theoretically, the ideal situation is obtained by applying high pressures with steep rise times to toners heated to temperatures at which their viscosity is substantially lowered so that they flow easily under the applied pressure into the paper. Of course, certain tradeoffs can be made. Thus, for example, very high pressures with fast rise times and toner heated to a minimum temperature could be used to achieve very low amounts of power. However, there are limits on the amount of pressure which can

be applied since excessive amounts deform copy paper causing it to curl and resulting in paper jams; also a good amount of mechanical stability is desirable in these machines and cannot be obtained if very large pressures are used.

Operating within the above general guidelines, it has been found that the toner should be preheated to a temperature sufficient to cause it to flow or to be driven into the copy paper to an appreciable depth under practical forces which can be applied. Preferably, toner is heated to a temperature at about its melting point or higher. For purposes of this description, the toner melting point is that temperature at which the toner has a viscosity of 14×10^9 centipoises.

In a like manner, the pressure applied should be sufficient to cause the heated toner to flow into the paper to an appreciable depth. When the toner is heated to a temperature around its melting point, it has been found that forces of 10 to 20 lbs. per linear inch applied to the pressure elements described herein result in excellent fusion. Additionally the pressure pulse should rise to a value of at least 150 lbs. per square inch in 10 milliseconds under these conditions, and preferably 200 lbs. per square inch in 5 milliseconds for reasons of thermal efficiency.

Figure 5 is a graphic representation of heat transferred to and from copy paper (Tp) as a function of time (t) in various toner transfer techniques. In Figure 5(a), a toner transfer technique of this invention is represented; Figure 5(b) represents a toner transfer technique as described in Byrne ('276); and Figure 5(c) represents a transfer and fusing technique wherein toner is electrostatically transferred to the copy paper and subsequently heat-fused as is done in many prior art methods.

In Figure 5(a), it can be seen that the temperature of the paper does not rise appreciably prior to the transfer zone. In the transfer zone, which is narrow, the paper temperature rises sharply, but never approaches the toner melting point. After toner transfer, the paper heats up slightly prior to its exit from the machine which helps to cool the belt. While Figure 5(a) represent a case with no preheating of the paper, even where the paper is preheated, however, it never is heated to the toner melting point and it still exits from the machine at a relatively low temperature.

In contrast, it can be seen in Figure 5(b) that in the Byrne preheating technique, the paper is heated prior to the transfer zone, which is wider, to a temperature above the melting point of the toner. Since the paper is heated to such a high value initially, it cools to a much lesser extent prior to exiting from the copy machine.

In Figure 5(c), it can be seen that the

70

75

80

85

90

95

100

105

110

115

120

125

130

paper is not heated prior to electrostatic transfer of toner. After transfer, the paper passes through a fusing zone during which the paper and toner are heated to a high temperature above the toner melting point so that the toner fuses to the paper.

Figure 6 is a plot of heat transfer to and from toner expressed in terms of the toner temperature (T_t) versus time (t) in the different zones of a transfer and fusing apparatus of this invention, the Byrne preheating technique, and in a customary electrostatic transfer and heat fusing apparatus. In Figure 6(a), it can be seen that the toner is heated to at least its melting point prior to the transfer zone. In the transfer zone, the toner cools below its melting point during transfer and fusion. Further cooling occurs in the cooling zone.

In contrast, Figure 6(b) illustrates that the Byrne transfer and fusing technique starts with temperature of the toner at ambient temperature prior to the transfer zone. In the transfer zone, heat is transferred from the preheated paper to the toner in sufficient quantities to heat the toner up to at least its melting point. Subsequent to transfer, the toner cools and fuses to the paper.

In Figure 6(c), it can be seen that electrostatic transfer does not result in the toner temperature being raised appreciably through the transfer zone. In the fusing zone, the temperature of the toner is elevated to at least its melting point, and subsequently the toner cools down prior to exiting from the machine.

Figure 7 illustrates in a graphical manner the type of pressure pulse found to be preferred with this invention in the second transfer operation, and that usually found in pressure transfer operations of the prior art, such as that described in the above-mentioned Byrne patent. In Figure 7(a) it can be seen that the pressure applying elements described herein produce a pressure pulse with a fast rise time and a fast decline. Thus, a pulse which is high and narrow results. As explained above, it has been found desirable to utilize this type of pressure transfer to mechanically drive the heated toner into the copy paper prior to its being able to cool substantially. In this manner, outstanding fusion is obtained.

On the other hand, Figure 7(b) illustrates a pressure pulse such as have been previously used. Since the force is applied over relatively wide contact area, the pulse is shorter and wider as illustrated. This type of pressure application is necessary in techniques where contact between paper and toner is relied upon to heat the toner above its melting point so that fusion will result.

Experimental runs have been made using toner transfer and fusing apparatus similar to that illustrated in Figure 1. Typical values

under equilibrium conditions are as follows. A toner image formed with Sun Chemical toner (m.p. 132°C.) is fed to an intermediate transfer belt from sheets of zinc oxide paper. The transfer belt consists of an aluminumized Kapton (Registered Trade Mark) substrate 0.002 inches thick coated with a 0.001 inch thick layer of Dow Corning 3140 silicone rubber. The transferred toner image is selectively preheated above its melting point by quartz-tungsten lamps supplied by a 1000 watt power source. The lamps are surrounded by a heat reflector. Plain, cold copy paper, 8 1/2 inches wide, is fed from a roll at a speed of 15 inches per second and brought into contact with the transfer belt at a point close to the exit of the radiant heater by a pressure bar having an edge of 0.075 inches and extending cross the width of copy paper. A 200 lb. force is applied on the bar. In these experiments, excellent transfer and fusion is accomplished.

There are many equivalents to the embodiments specifically described herein which fall within the scope of the following claims. One example relates to the type of heater used. Whereas radiant heaters have been specifically illustrated, it will be recognized by those skilled in the art that microwave heaters could be used, because most of the transfer member materials have low dielectric loss tangents. If used, microwave heaters should have cavities designed to concentrate the microwave field. Also, it would be preferable to use toners having higher than normal amounts of carbon black with microwave heaters, such as the 65% polystyrene, 35% carbon black toner described at col. 7, lines 33-35 of Donnelly et al., U.S. 3,669,707. Other equivalents within the scope of the claims will be known or easily determined by no more than routine experimentation by those skilled in the art.

WHAT WE CLAIM IS:—

1. A method for transferring and fusing a non-fused toner image from a first support material to a second support material, comprising transferring toner from said first support material to an intermediate transfer member having a smooth surface with a surface free energy of below 40 dynes per centimeter, a hardness of from 3 to 70 durometers, and a heat capacity of below 3.1×10^{-2} calories/cm²/°C.; selectively preheating toner on said intermediate transfer member to at least its melting point temperature; and, bringing said second support material into pressure contact with heated toner on said intermediate transfer member in a manner sufficient to thereby transfer and fuse toner to said second support material.

2. A method according to Claim 1, wherein toner is transferred from said first support material to said intermediate transfer mem-

ber by bringing said intermediate transfer member into pressure contact with said first support material.

5 3. A method according to Claim 1 or 2, wherein the surface of the intermediate transfer member comprises an elastomeric member.

10 4. A method according to any preceding claim wherein said selective preheating comprises radiant heating.

15 5. An intermediate toner transfer member characterized by a flexible, mechanically and thermally stable material and having a smooth surface with a free energy below 40 dynes per centimeter, a hardness of from 3 to 70 durometers, and a heat capacity below 3.1×10^{-3} calories/cm²/°C.

20 6. An intermediate transfer member according to Claim 5, wherein the surface of said member comprises a fluorelastomer.

7. An intermediate transfer member according to Claim 5, wherein the surface of said member comprises an elastomeric material.

25 8. An intermediate transfer member according to Claim 7, wherein said elastomeric material comprises a silicone rubber from 0.5 to 2 mils thick.

30 9. An intermediate transfer member according to Claim 8 wherein said silicone rubber is coated upon a substrate comprising a polyimide film having a thickness of from 0.5 to 5 mils.

35 10. An intermediate transfer member according to Claim 9, wherein said silicone rubber is transparent and wherein said polymeric substrate is coated with a reflecting layer.

40 11. An apparatus for transferring a non-fused xerographic toner image from a first support material to a second support material and fusing the toner image to the second support material comprising an intermediate transfer member positioned to receive toner from said first support material, said intermediate transfer member having a smooth surface with a surface free energy of below 40 dynes per centimeter, a hardness of from 3 to 70 durometers, and a heat capacity of below 3.1×10^{-3} cal/cm²/°C; means for transferring toner from said first support material to said intermediate transfer member; means for heating toner on said intermediate transfer member to a temperature at which it flows prior to transfer to said second support material, means for supplying second support material; and pressure means for bringing said second support material into pressure contact with heated toner on said intermediate transfer member in a manner whereby toner is transferred and fused to the second support material.

60 12. An apparatus according to claim 11, wherein said pressure applying element comprises a pressure bar.

13. An apparatus according to Claim 11, wherein said pressure applying element comprises a pinch roller.

14. An apparatus according to any one of Claims 11 to 13 wherein said intermediate transfer member has an elastomeric surface. 70

15. An apparatus according to Claim 14 wherein said elastomeric surface comprises a silicone rubber. 75

16. An apparatus according to any one of Claims 11 to 15, wherein said intermediate transfer member is a drum.

17. An apparatus according to any one of Claims 11 to 15, wherein said intermediate transfer member is a flexible belt positioned to come into pressure contact with said second support material. 80

18. An apparatus according to Claim 17, wherein said belt has a substrate comprising polyimide film. 85

19. An apparatus according to Claims 17 to 18, wherein said substrate is coated with a reflecting layer.

20. An apparatus according to any one of Claims 17 to 19, wherein said intermediate transfer belt comprises a polyimide substrate, a reflecting layer, and a transparent silicone rubber, said polyimide substrate having a thickness of from 0.5 mils to 5 mils and said silicone rubber having a thickness of from 0.1 mils to 10 mils. 90 95

21. An apparatus according to Claim 20, wherein said second support material comprises paper. 100

22. An apparatus according to any one of Claims 11 to 21, wherein said first support material comprises a photoconductive insulating surface.

23. An apparatus according to Claim 22 wherein said photoconductive insulating surface comprises zinc oxide. 105

24. An apparatus according to Claim 22, wherein said photoconductive insulating surface comprises vitreous selenium. 110

25. An apparatus according to any one of Claims 22 to 24, wherein the means for bringing the second support material into pressure contact with heated toner on the intermediate member comprises a zone subsequent to the specific pressure applying element in which said intermediate transfer member and said second support material remain in contact. 115

26. An apparatus according to Claim 25, wherein said means causes said intermediate transfer member and said second support member to remain in contact for at least 0.5 seconds. 120

27. An apparatus especially suitable for use in electrophotographic copying processes wherein multiple toner images on a photoconductive material are transferred from a first support material to a second support material for each exposure of the photoconductive 125 130

- material, wherein an intermediate transfer member, at least a portion of which is positioned adjacent to said first support material, said intermediate transfer member having a smooth surface with a surface free energy of below 40 dynes per centimeter, a hardness of from 3 to 70 durometers, and a heat capacity of below 3.1×10^{-3} calories $\text{cm}^2/\text{°C.}$; means for bringing said intermediate transfer member into pressure contact with said first support material including means to vary the amount of pressure between said first support material and said intermediate transfer member whereby the amount of toner transferred from said first support material to said intermediate transfer member can be controlled; means for heating toner transferred to said intermediate transfer member, means for supplying second support material; means for bringing said second support material into pressure contact with toner on said intermediate transfer member whereby toner is transferred and fused to said second support material; and means for retoning portions of the initial toner image remaining on said first support material after it contacts said intermediate transfer member. 25
28. A method for transferring and fusing a non-fused toner image as claimed in claim 1 and substantially as hereinbefore described. 30
29. An intermediate toner transfer member as claimed in Claim 5 and substantially as hereinbefore described with reference to the accompanying drawings.
30. Apparatus for transferring and fusing a non-fused toner image as claimed in claim 11 and substantially as hereinbefore described with reference to the accompanying drawings. 35
- MICHAEL BURNSIDE & PARTNERS,
Chartered Patent Agents,
Hancock House,
87 Vincent Square,
London, SW1P 2PH,
Agents for the Applicants.

Printed for Her Majesty's Stationery Office, by the Courier Press, Leamington Spa, 1976.
Published by The Patent Office, 25 Southampton Buildings, London, WC2A 1AY, from which copies may be obtained.




FIG. 1.






FIG. 3.






FIG. 5.




FIG. 6.




FIG. 7.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.